# medusa

- **-c** — Time to wait in usec to verify socket is available (default 500 usec).
- **-r** — Sleep NUM seconds between retry attempts (default 3)
- **-M** — Name of the module to execute (without the .mod extension)
- **-e** — Additional password checks ([n] No Password, [s] Password  Username)
- **-O** — File containing combo entries. See README for more information
- **-g** — Give up after trying to connect for NUM seconds (default 3)
- **-C** — File containing combo entries. See README for more information
- **-P** — File containing passwords to test
- **-p** — Password to test
- **-L** — Parallelize logins using one username per thread. The default is to process the entire username before proceeding.
- **-b** — Suppress startup banner
- **-q** — Display module's usage information
- **-w** — Error debug level [0 - 10 (more)]
- **-Z** — Resume scan based on map of previous scan
- **-U** — File containing usernames to test
- **-h** — Target host-name or IP address
- **-f** — Stop scanning host after first valid username/password found.
- **-R** — Attempt NUM retries before giving up. The total number of attempts will be NUM + 1.
- **-m** — Parameter to pass to the module. This can be passed multiple times with a different parameter each time and they will all be sent to the module
- **-d** — Dump all known modules
- **-r** — Sleep NUM seconds between retry attempts (default 3)
- **-n** — Use for non-default TCP port number
- **-s** — Enable SSL
- **-H** — File containing target hostnames or IP addresses
- **-u** — Username to test
- **-t** — Total number of logins to be tested concurrently
- **-F** — Stop audit after first valid username/password found on any host.
- **-v** — Verbose level [0 - 6 (more)]
- **-V** — Display version

www.hackingarticles.in